

श्रमःधारण

EXTRAORDINARY

भाग II--खण्ड 3--- उपखण्ड (ii)

PART II—Section 3—Sub-section (ii)

प्राधिकार से प्रकाशित

PUBLISHED BY AUTHORITY

सं**० 117] नई दिल्ली, बृहस्पतिवार, अ**प्रैल 4, 1968/चैश्र 15, 1890

No. 117] NEW DELHI, THURSDAY, APRIL 4, 1968/CHAITRA 15, 1890

इस भाग में भिन्न पुष्ठ संख्या वी जाती है जिससे कि यह ग्रलग संकलन के रूप में रखा जा सके।

Separate paging is given to this Part in order that it may be filed as a separate compilation.

MINISTRY OF COMMERCE

NOTIFICATIONS

New Delhi, the 4th April 1968

- **5.0.** 1297.—In exercise of the powers conferred by section 6 of the Export (Quality Control and Inspection) Act, 1963 (22 of 1963) and after previous publication as required by sub-rule (2) of rule 11 of the Export (Quality Control and Inspection) Rules, 1964, the Central Government hereby makes the following amendment to the notification of the Government of India in the Ministry of Commerce S.O. 847 dated the 13th March, 1967, namely:
 - 1. In the said notification-
 - (i) for paragraph 3, the following paragraph shall be substituted, namely:--
 - "3. For the purpose of this notification "rubber beltings" shall mean any of the beltings mentioned in Annexure I to this notification made from woven canvas or woven solid by interweaving layers of cotton and/or hair and binders impregnated with rubber linseed base/bituminous compound etc. with or without rubber cover, the whole being vulcanised/processed together in a uniform manner, used for the purpose of conveying materials or power transmission".
 - (ii) In Annexure I, after serial No. 2 and the entries relating thereto, the following serial number and the entries relating thereto shall be added, namely:—
 - "3. Solid woven impregnated cotton belting.
 - 4. Solid woven impregnated hair belting."

- (iii) in Annexure II, after serial No. B and the entries relating thereto, the following serial number and the entries relating thereto shall be added, namely:—
 - "C. Specification for solid-woven impregnated cotton belting.
- Construction.—The belting shall be made from high grade cotton yarn, well
 and evenly spun, and free from foreign matter or defects and shall be fully impregnated with rubber or linseed base or bituminous compound.
- 2. Requirements.—The belting shall conform to the requirements specified below:—
- 2.1. Dimensions and Tolerances.—The dimensions of the belting shall be as specified by the purchaser subject to the following tolerances:
- 2.1.1. Length.—The length of the belting shall be as agreed to between the buyer and seller.
- 2.1.2. Width.—The width of the belting shall be as agreed to between the buyer and seller with the following tolerances:

Width

Tolerances

(a) Upto and including 125 mm.

1.6 mm.

(b) Above 125 mm.

3.2 mm.

- 2.2. Tensile Test.—The ultimate tensile stress of the belting shall be not less than 5.27 kg/mm² of nominal cross section.
- 2.3. Elongation.—The elongation of belting shall be not less than 2 percent and not more than 6 percent.
 - D. Specification for solid-woven impregnated hair belting.
- 1. Construction.—The belting shall be woven solid by inter-weaving layers of cotton and/or hair and binders and shall be fully impregnated with rubber or linseed base or bituminous compound.
- 2 Requirement.—The belting shall conform to the requirement specified below:—
- 2.1 Dimensions and Tolerances.—The dimensions of the belting shall be as specified by the purchaser subject to the following tolerances:
- 2.1.1. Length.—The length of the belting shall be as agreed to between the buyer and seller.
- 2.1.2. Width.—The width of the belting shall be as agreed to between the buyer and seller with the following tolerances:

Width

Tolerance

(a) Upto and including 125 mm.

1.6 mm.

(b) Above 125 mm.

3.2 mm.

- 2.2. Tensile Test.—The ultimate tensile stress of the belting shall be not less than $3 \text{ kg}/\text{mm}^2$.
- 2.3. Elongation.—The elongation of the belting shall be not less than 4 percent and not more than 10 per cent."
 - 2. This notification shall come into force on 22nd April, 1968-

[No. 60(28)/Exp. Insp./67.]

- **S.O.** 1298.—In exercise of the powers conferred by Section 17 of the Export (Quality Control and Inspection) Act, 1963 (22 of 1963), the Central Government hereby makes the following rules further to amend the Export of Rubber Belting (Inspection) Rules, 1966, namely:—
- 1. These rules may be called the Export of Rubber Belting (Inspection) Amendment Rules, 1968.
 - 2. In the Export of Rubber Belting (Inspection) Rules, 1966-
 - (1) For rule 2 the following rule shall be substituted namely:—
 - "2 Definition—In these rules "rubber beltings mean any of the beltings mentioned in Schedule to these rules made from woven canvas or

woven solid by interweaving layers of cotton and/or hair and binders impregnated with rubber/linseed base/bituminous compound etc-with or without rubber cover, the whole being vulcanised/processed together in a uniform manner used for the purpose of conveying materials or power transmission."

- (2) In THE SCHEDULE after serial No. 2 and the entries relating thereto, the following serial numbers and the entries relating thereto shall be added namely—
- "3. Solid woven impregnated cotton belting.
- 4. Solid woven impregnated hair belting."

[No. 60(28)/Exp. Insp./67.]

S.O. 1299.—In exercise of the powers conferred by Scction 7 of the Export (Quality Control and Inspection) Act, 1963 (22 of 1963), the Central Government hereby makes the following amendment in the Notification of the Government of India in the Ministry of Commerce S.O. 849 dated 13th March, 1967, namely:—

In the said notification in Schedule II after serial number 2 and the entries relating thereto, the following serial numbers and the entries relating thereto shall be added, namely—

- "3. Solid woven impregnated cotton belting-
 - 4. Solid woven impregnated hair belting."

[No. 60(28)/Exp. Insp./67.] A. C. BANERJEE, Jt. Secy